




#### Dimensions (mm)



Model 66					
Α	318	D	185		
В	168	Е	131		
С	64				

InSinkErator reserves the right to change product specifications without prior notice. The disposer described in this leaflet is for household use: usage in commercial situations is not covered by warranty.

# Model 66

## Category Benefits

- Food waste is ground into particles and flushed away in seconds
- Clean, hygienic, convenient and simple to use
- Easy method to manage food waste in the home, saving you time and helping to minimise trips to the outside dustbin
- Permanent in-house solution that is compact and sits under the sink without taking up valuable storage
- Easy to install into new or existing kitchens and can be fitted to most sinks
- Environmentally responsible, helping reduce the amount of waste that goes to landfill sites

## Features

- 1-stage grind technology
- High-torque Dura-Drive® induction motor
- Built-in air switch in chrome and brushed steel
- 4 Year guarantee
- · Stainless steel grind elements
- · Continuous feed
- Overload protection
- Quick Lock® mounting assembly for faster, easier installation
- Cast lugs
- · Removable sound baffle

### Sample Specification

Food waste disposer(s) shall be InSinkErator® Model 66 with 1-stage grind technology, .75 hp motor, auto-reverse grind system, stainless steel grind elements and built-in air switch with chrome and brushed steel options.

Guarantee: 4 Year parts and service.

The complete InSinkErator guarantee is included in the Care & Use Booklet packed with each unit.

#### Specifications

Type of Feed	Continuous	
On/Off Control	Built-In Air Switch	
Motor	Single Phase	
Time Rating	Intermittent	
Lubrication	Permanently Lubricated Upper & Lower Bearings	
Shipping Weight (Approx.)	8.2 kg	
Overall Height	318 mm	
Grind Technology	1-Stage Grind Technology	

Grind Chamber Capacity	980 ml	
Motor Protection	Manual Reset Overload	
Average Water Usage	Approximately 4.0 L per Person per Day	
Average Electrical Usage	3-4 KWH per Annum	
Drain Connection	1-1/2" (3.81 cm)	
Dishwasher Drain Connection	Yes	

Volts/Hz	HP	RPM	Average Load
120V, 60 Hz	.75	1725	8.1 A
220-240V, 50 Hz	.75	1425	405 W
220-240V, 60 Hz	.75	1725	405 W

InSinkErator Australia 471 Mountain Highway Bayswater Vic 3153, Australia Sales/Service Tel: 1300 136 205 Sales/Service Fax: (03) 9720 3178 Website: www.insinkerator.com.au

Find us on facebook at facebook.com/insinkeratorAU

InSinkErator Division Emerson Electric Co. 4700 21st Street Racine, WI 53406-5093 USA Sales/Service Tel: 262-554-3652 www.insinkerator.com/worldmap.html Download a QR Reader App to Smartphone



EMERSON.